

CAT6A UTP Patch Cord





DATA SHEET

L +44 20 8895 6455

info@webbinfra.com

 info@webbinfra.com

⊕ www.webbinfra.com



CAT6A UTP Patch Cord

WEBB CAT6A Unshielded UTP patch cord are designed to meet and exceed ANSI/TIA/EIA 568B standards. WEBB patch cords are made by high-quality patch cable and RJ45 modular plug. These cables are simple, cost effective, reliable provides high speed transmission of data.

Features

- 500 MHz with over 10Gbps
- Unshielded twisted pair cable
- LSZH, PVC, PE jackets
- RJ45 Connectors Flash gold plated
- Available in different colors, reel lengths and reeling technics
- Durable for 750 insertion cycles

Applications

- Data centre and telecommunication networks
- LAN applications
- CATV cable television, CCTV

Technical Specifications

Operating life	750 Insertion cycle
Dielectric pair	4 pairs
Conductor	Copper (0.127±0.005mm)
Contact material	Phosphor bronze
Contact plating	60u inch gold
Overall diameter	5.7±0.30mm
Bending radius	15xOD
Contact resistance	30m Ω
Uninsulated resistance	$150~{ m M}\Omega/{ m km}$ minimum
Connector	RJ45
Jacket material	PVC/LZOH/PE
Cabling standard	EIA/TIA 586B
Flame retardance, smoke emission	IEC 60332-1, IEC 61034
Typical applications	IEEE 802.3: 10BASE-T; 100BASE-T; 1000BASE-T

^{*}Specifications are subject to change without notice based on technical recommendations and related product enhancements



PATCH CORDS PART NUMBER KEY

Part Number: C.04._ _._ .. _..

C.04.Cable.Cable Contruction.Length.Sheath.Color

Please add the codes from the tables below in the above format to derive at your desired product part number

Cable	Code
CAT6	C6
CAT6A	CA
CAT7A	C7

Sheath	Code
PVC	P
LZOH	L

Cable Construction	Code
UTP	UT
FTP/UFTP	FT
FFTP	FF
SFTP	SF
FLAT / LIFT	FLAT

Color	Code
Grey	G
Blue	В
Custom	С

Length	Code
1 meter	01
2 meter	02
3 meter	03
5 meter	05
Custom	0C

^{*}Specifications are subject to change without notice based on technical recommendations and related product enhancements