



CAT6 Flat Travelling Cable



DATA SHEET

+44 20 8895 6455
info@webbinfra.com
www.webbinfra.com

CAT6 Flat Travelling Cable

Technical Specification

No. of conductors	9
Conductor size	0.15mm +/- 0.02mm
Conductor	Bare copper
No. of pair	1 x 4pr
Insulation type	PE
Insulation color	Pair 1 : Brown – white/brown Pair 2 : Green – white/green Pair 3 : Blue – white/blue Pair 4 : Orange – white/orange
Insulation diameter	1mm +/- 0.10mm
Core sheath type	PVC
Core sheath color	Pair 1 : Brown Pair 2 : Green Pair 3 : Blue Pair 4: Orange
Core sheath diameter	2.40mm +/- 0.20mm
Core identifications	Color
Outer sheath diameter	12.60mm x 4.25mm (Approx)
Outer sheath color	Grey
Outer sheath dimension	As per EN 50214
Packing	1000 Meters drum
Free suspension length	Max.45 m
Running speed	Upto 4 m/s

**Specifications are subject to change without notice based on technical recommendations and related product enhancements*



Features

- Flexible for travelling
- Soft-annealed electrolytic copper conductor
- Insulation with properties according to EN 50214
- Printing: CAT6-E CABLE <WEBB > CE RoHS ANTIRODENT <H03EVH6-F> Batch No.1294 09/2019

Ordering Information

Part number	Description
C.04.C6.ND.FLAT.PG	CAT6 Flat Travelling Cable

**Specifications are subject to change without notice based on technical recommendations and related product enhancements*