

CAT6 UTP Patch Cord





DATA SHEET

44 44 20 8895 6455

info@webbinfra.com

info@webbinfra.com

⊕ www.webbinfra.com



CAT6 UTP Patch Cord

WEBB CAT6 unscreened UTP patch cords are designed to meet and exceed ANSI/TIA/EIA 568B standards. WEBB patch cords are made by high-quality patch cable and RJ45 modular plug. These cables are simple, cost effective, reliable provides high speed transmission of data.

Features

- 250 MHz with over 2.5Gbps
- 4 pairs unshielded twisted pair cable
- LSZH, PVC, PE jackets
- RJ45 Connectors Flash gold plated
- Durable for 750 insertion cycles
- 24 AWG conductor
- Available in different colors, reel lengths and reeling technics

Applications

- Data centre and telecommunication networks
- LAN applications
- CATV cable television, CCTV

Technical Specifications

Conductor	24AWG
Dielectric material	Foamed polyethylene
Operating life	750 Insertion cycle
Dielectric pair	4 pairs
Conductor material	Copper
Contact material	Phosphor bronze
Contact plating	60u inch gold
Overall diameter	5.1±0.05mm
Connector	RJ45
Jacket material	PVC
Cabling standard	EIA/TIA 586B
Flame retardance, smoke emission	IEC 60332-1, IEC 61034
Typical applications	IEEE 802.3: 10BASE-T; 100BASE-T; 1000BASE-T

^{*}Specifications are subject to change without notice based on technical recommendations and related product enhancements



Ordering Information

Part number	Description
C.04.C6.UT.01.P.G(A)	Patch Cord CAT6 UTP 24AWG 1m PVC - Grey
C.04.C6.UT.03.P.G(A)	Patch Cord CAT6 UTP 24AWG 3m PVC - Grey

^{*}Specifications are subject to change without notice based on technical recommendations and related product enhancements