

Speaker Cable Meridian Mobile SP225; 2 x 2,50 mm²; PVC Ø 7,80 mm; black**ADVANTAGES:**

- flexible and easy to rollable for cable reel
- Small in diameter
- Very durable due to the use of special coating mixtures
- Affordable price

APPLICATION:

- PA sound systems of all kinds
- For ELA technology
- Cabling of HiFi systems

SPECIFICATIONS

Name	Meridian Mobile SP225
Properties	OFC oxygen free copper
Properties	Analog
Application area	Stage / live
Application area	ELA 100 V
Application area	Studio / Broadcast
Application area	Mobile outdoor / indoor
Application	Speaker Cable
Colour	black
Colour detailed	black
Construction	(2LIY2,5mm ²)Y
Jacket material	PVC
Jacket Ø [mm]	7,80
Number of Channels (audio)	1
Inner conductor (audio)	2
Inner conductor (audio) [mm²]	2,50
Inner conductor Ø (audio) [mm]	1,78

AWG (audio)	13
Copper strands (audio)	140
Copper strand Ø (audio) [mm]	0,15
Conductor insulation Ø [mm]	3,05
Weight per 1 m [g]	106
UV-resistant	yes
Fire load per m [kWh]	0,33
Style variant	round
Packing	100 m spool
Packing	500 m spool
Temperature min. [°C]	-30
Temperature max. [°C]	70
Width [mm]	7,8
Height [mm]	7,8
Capac. cond./cond. per 1 m (audio) [pF]	136
Capacity wire/wire at 1 ft. (audio) [pF]	41,4528
Insulation resist. per 1 km [GΩ]	0,005
Insulation resist. per 1000 feet [GΩ]	0,0015
Insulation resist. per 1 km (audio) [GΩ]	0,005
Insulation resist. per 1000 feet (audio) [GΩ]	0,0015
Conductor resistance per 1 km [Ω]	7,5
Conductor resistance per 1000 ft. [Ω]	2,286
EAN	4049371050944