

Factory: Wynnstay Technology Park Ruabon, Wrexham United Kingdom LL14 6EN +44 (0) 1978 810789

+44 (0) 1978 821502

Tel: Fax: Email:


Web:

sales@wrexhammineralcables.com www.wrexhammineralcables.com

## Low Smoke Zero Halogen (LSZH)

## **Sizes**

RHGMM LSZH shrouds are a low smoke zero halogen shroud which are used during installation to cover the cable glands giving a neat professional finish. The RHGMM LSZH shroud comes in various sizes and colours.





Size	Description	Part Number	Hole size	Min Wall
				thickness
20mm	LSZH Shroud	RHGMM20/Colour	21.5mm	1.0mm
25mm	LSZH Shroud	RHGMM25/Colour	27.2mm	1.0mm
32mm	LSZH Shroud	RHGMM32/Colour	35.5mm	1.0mm
40mm	LSZH Shroud	RHGMM40/Colour	46.0mm	1.0mm

## **Material Properties**

Grade	Halogon Fron	
	Halogen Free	
Colour	Black Red Orange & White	
Hardness (IRHD)	65 m- 70 Shore A	
Modulus Mpa	No Data Available	
Tensile Strength Mpa	7 Min	
Tear Strength	23 n/m	
Elongation @ Break %	400 Min	
High Temp use (Con)	+250c	
High Temp use (Peak)	+275c	
Low Temp Flexibility	-60c	
Oxygen Index	32	
UL Rating	Not Tested	
Smoke Evolution	Low Smoke Ao <o. 029<="" td=""></o.>	
Food Quality	No	
Medical	No	
Oil Resistant	Fair	
Dielectric Strength	High	
Ozone Resistance	Excellent	
Halogen Content	<0.5	