

RPS Seal kits

Description

RPS seals (commonly know as standard seals) are designed to be used in conjunction with Wrexham Mineral Cables glands. Manufactured and tested to BS EN 60702-2:2002.

For ambient service temperatures of -20°C to 105°C

Dependent on the cable size the pots are supplied in 20mm 25mm 32mm and 40mm



Contents

The seal kit contains the following as standard

ITEM DESCRIPTION	QTY
RPS POTS	20mm pots x 10, 25 32 & 40mm pots x 2
SEAL OR STUB CAPS (SIZE DEPENDANT)	20mm pots x 10, 25 32 & 40mm pots x 2
RMX SEALING COMPOUND	20mm pots x 3 sticks, 25 32 & 40mm pots x 2
PVC SLEEVING	Dependent on cores - either 2 or 3 hanks of 1.5m

Light Duty Cables

CABLE REFERENCE	SEAL NEEDED
2L1	RPS2L1
2L1.5	RPS2L1.5
2L2.5	RPS2L2.5
2L4	RPS2L4
3L1	RPS3L1
3L1.5	RPS3L1.5
3L2.5	RPS3L2.5
4L1	RPS4L1
4L1.5	RPS4L1.5
4L2.5	RPS4L2.5
7L1	RPS7L1
7L1.5	RPS7L1.5
7L2.5	RPS7L2.5

Heavy Duty Cables

CABLE REFERENCE	SEAL NEEDED
2H1.5	RPS2H1.5
2H2.5	RPS2H2.5
2H4	RPS2H4
2H6	RPS2H6
2H10	RPS2H10
3H1.5	RPS3H1.5
3H2.5	RPS3H2.5
3H4	RPS3H4
3H6	RPS3H6
3H10	RPS3H10
4H1.5	RPS4H1.5
4H2.5	RPS4H2.5
4H4	RPS4H4
4H6	RPS4H6
4H10	RPS4H10
4H16	RPS4H16
4H25	RPS4H25

Single Core Cables

CABLE REFERENCE	SEAL NEEDED
1H2.5	RPS1H2.5
1H4	RPS1H4
1H6	RPS1H6
1H10	RPS1H10
1H16	RPS1H16
1H25	RPS1H25
1H35	RPS1H35
1H50	RPS1H50
1H70	RPS1H70
1H95	RPS1H95
1H120	RPS1H120
1H185	RPS1H185
1H240	RPS1H240

Other sizes available on request